



- NOTES:**
- 1)DRAWING SHOWS B7 MDA ENCLOSURE DESIGNED TO IP44 C/W END BOX AND OPTIONAL 600mm HIGH STAND EXTENSION.
  - 2)FITTED WITH REMOVABLE GLAND PLATES SECURED WITH M6x20 HEX HD. BOLTS.
  - 3)INCOMING CABLE ACCEPTANCE: 3x400mm<sup>2</sup> 4 CORE OR 24x400mm SINGLE CORE. WITH SINGLE HOLE (M16) FIXING CABLE LUGS CATERED FOR AS STANDARD. ALLOWANCE FOR OTHER PATTERNS CAN BE ACCOMMODATED ON REQUEST.
  - 4)TYPICAL WEIGHT: 520KG (BASED ON 1600A MDA)
  - 5)600mm HIGH STAND EXTENSION SHOWN IS SOLD SEPARATELY AS ITEM 'S140308SE' AND ADDS APPROXIMATELY 60kg TO THE MDA WEIGHT.

CUSTOMER INFORMATION COPY

REV: A	EDR: 8248	MATERIAL: MILD STEEL	SIZE:
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. TOLERANCES TO H30052		REF: S140308R	COPY ISSUED: 10 Jan 2022
FIXING STANDARD TO H30051 WIRING STANDARD TO H20051 WELDING STANDARD TO QAI 061.		ORIGINAL SCALE: 1:10	DATE: 10/01/22
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK		<b>BLAKLEY ELECTRICS LIMITED</b>	
TITLE: GENERAL ASSEMBLY B7 MDA			
DRN: P.R.	CHKD: P.R.	DRAWING No. A32529	REVISION: A
APPD: [Signature]			