



NOTES:
 TERMINATION DISTANCE – 295mm
 MAX CABLE ACCEPTANCE – 50mm RIGID OR 35mm FLEXIBLE
 IP RATING – IP54

REV:	-																			
EDR:	-																			
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. TOLERANCES TO H30052 FIXING STANDARD TO H30051 WIRING STANDARD TO H20051 WELDING STANDARD TO QAI 061.												MATERIAL		SIZE						
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK												REF. S201150R		COPY ISSUED 18 Mar 2020						
TITLE GENERAL ASSEMBLY SRC 100A kWhr												ORIGINAL SCALE 1:6		BLAKLEY ELECTRICS LIMITED						
												DATE. 20/02/20								
												DRN. P.R		DRAWING No. B32402		REVISION				
												CHKD.								
												APPD. RWA								

THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT WITHOUT THEIR WRITTEN CONSENT BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE. THIS COPY IS UNCONTROLLED UNLESS OTHERWISE MARKED.

CUSTOMER INFORMATION COPY