



NOTES:

- 1) DRAWING SHOWS B2 MDA TYPICAL ENCLOSURE WITH DOLLY COVER DESIGNED TO IP55.
- 2) FITTED WITH 4P 125A SWITCH DISCONNECTOR WITH TUNNEL TYPE TERMINALS
- 3) MAXIMUM CABLE SIZE - 50mm SOLID/STRANDED OR 35mm FLEXIBLE
- 4) FITTED WITH REMOVABLE GLAND PLATES AND SOCKET PLATES.
- 5) FIT LABELS IN POSITION'S AS DETAILED

THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT WITHOUT THEIR WRITTEN CONSENT BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE. THIS COPY IS UNCONTROLLED UNLESS OTHERWISE MARKED.

REV: -											
EDR: -											
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. TOLERANCES TO H30052 FIXING STANDARD TO H30051 WIRING STANDARD TO H20051 WELDING STANDARD TO QAI 061.							MATERIAL MILD STEEL		SIZE		
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK							REF. S140520	COPY ISSUED 19 Nov 2019			
TITLE GENERAL ASSEMBLY B2/1125-4P C9-RCD/S9-32/IP55							ORIGINAL SCALE 1:8	BLAKLEY ELECTRICS LIMITED			
							DATE. 06/11/19			DRAWING No. C27997	
							DRN. P.R				
							CHKD.				
							APPD. P.W.A				