



NOTES:

- 1) DRAWING SHOWS B3 MDA TYPICAL ENCLOSURE WITH DOLLY COVER DESIGNED TO IP55.
- 2) FITTED WITH REMOVABLE GLAND PLATES AND SOCKET PLATES.
- 3) FIT LABELS IN POSITIONS AS DETAILED
- 4) MAXIMUM RECOMMENDED CABLE SIZE: 150mm 4C SWA USING NARROW PALM CABLE LUGS.

THIS DRAWING IS THE PROPERTY AND COPYRIGHT OF BLAKLEY ELECTRICS AND MUST NOT WITHOUT THEIR WRITTEN CONSENT BE PASSED ON, COPIED, OR USED FOR ANY OTHER PURPOSE. THIS COPY IS UNCONTROLLED UNLESS OTHERWISE MARKED.

REV:	-																							
EDR:	-																							
UNLESS OTHERWISE STATED:- ALL DIMENSIONS IN MM. TOLERANCES TO H30052 FIXING STANDARD TO H30051 WIRING STANDARD TO H20051 WELDING STANDARD TO QAI 061.												MATERIAL		MILD STEEL							SIZE			
DO NOT SCALE THIS DRAWING. IF IN DOUBT, ASK												REF.		S140714		COPY ISSUED		19 Nov 2019						
TITLE												ORIGINAL SCALE		1:10		BLAKLEY ELECTRICS LIMITED								
GENERAL ASSEMBLY B3/1250-4P C15-RCD/S15/IP55												DATE.		07/11/19										
												DRN.		P.R		DRAWING No.		C28000						
												CHKD.				REVISION								
												APPD.		RWA										