

### Portable and Pre-Wired 110V LED Floodlights

A range of pre-wired, 110V, LED floodlights rated at 18W, 30W, 50W and 70W. The single floodlights are supplied on a cradle bracket and can be tripod, scaffold or wall mounted. An additional bracket is required for scaffold mounting (see below). The 18W floodlight is available in twin tripod mounting format. Assemblies are pre-wired with yellow input leads complete with 16A 110V plug. The overall assemblies are rated to IP44 and are suitable for indoor or outdoor use. Light outputs are as follows:

- 18W - 1500 lumens (each)
- 30W - 2700 lumens
- 50W - 3750 lumens
- 70W - 5250 lumens

When higher wattage LED floodlights are to be tripod mounted, please refer to data sheet SLDS033, which details our heavy duty 5m Portalite tripod and LED floodlights rated from 100W to 300W. When fitted to 5m tripods, LED floodlights are mounted on purpose built cross arms, which are securely clamped to the tripod mast to provide a robust mounting arrangement, which is a requirement when fitting luminaires above 3m in height.



Twin 18W and Tripod - S061040 + S210018



18W LED Floodlight - Part No. S061039



50W LED Floodlight - Part No. S060986E

#### Part Numbers

Part No.	Type	Description
S061039	LED/18/110/3/16	18W LED wall / tripod / scaffold mounting c/w 3m cable and a 16A 110V plug
S061040	LED/2/18/110/3/16	Twin 18W LED, tripod mounting c/w 3m cable and a 16A 110V plug
S060937	LED30/110/3/16	30W LED wall / tripod / scaffold mounting c/w 3m cable and a 16A 110V plug
S060986E	LED/50/YELL/110/5/16	50W LED wall / tripod / scaffold mounting c/w 5m cable and a 16A 110V plug
S060987E	LED/70/YELL/110/5/16	70W LED wall / tripod / scaffold mounting c/w 5m cable and a 16A 110V plug
S210018	THCMT	Tripod, Telescopic, Swing Leg, 2.3m
S060189	Scaffold Clamp	Half Swivel Scaffold Clamp
S060223	Fixing Kit, M8	To fix S060937 or S061039 to S060189
S060618	Fixing Kit, M10	To fix S060986 or S060987 to S060189